



JKL PART NUMBER	COLOR RGB WHITE	STARTING CIRCUIT VOLTAGE VS (Vrms)	OPERATING LAMP VOLTAGE VL (Vrms)	OPERATING LAMP CURRENT IL (mAmps)	BRIGHTNESS (CANDELA/m2)	*RATED LIFE (HRS)
BF22316-29B	x = .312 y = .305	1830 @ 0°C	732	5 ± 1	35,000 ±10%	20,000

* RATED LIFE IS DEFINED AS THE POINT AT WHICH THE INTENSITY BECOMES 50% OF THE INITIAL RATING.

 THIRD ANGLE PROJECTION		METRIC DIMENSIONS ARE IN MILLIMETERS TOLERANCE UNLESS OTHERWISE SPECIFIED 1 PL +/- 0.2 2 PL +/- 0 ANGLE +/- 0		JKL COMPONENTS CORPORATION				
DRAWN BY L. WENGSTROM		APPVD BY L.R.		DATE 1/23/08	SIZE A	FSCM NO. 55335	DRAWING NO. BF22316-29B	
RELEASE & CANCEL P-0709-05		1/23/08		- CAD DRAWING -			SCALE NONE	
REV. NO.	DESCRIPTION/ECO NUMBER	APPVD DATE	MANUAL REVISIONS NOT PERMITTED		RELEASED DATE 1/23/08	REVISION DATE	REV. NO.	SHEET 1 OF 1