


JKL LAMP PART NUMBER	COLOR	STARTING CIRCUIT VOLTAGE VS (Vrms)	OPERATING LAMP VOLTAGE VL (Vrms)	OPERATING LAMP CURRENT IL (mA rms)	BRIGHTNESS (CANDELA/m ²)	*RATED LIFE (HRS)
BF3220-29B	x = 0.312±0.03 y = 0.307±0.03	1100 @ 0°C	450	5 ± 1	TYP = 29,000 MIN = 20,300	20,000

* RATED LIFE IS DEFINED AS THE POINT AT WHICH THE INTENSITY BECOMES 50% OF THE INITIAL RATING.

METRIC



THIRD ANGLE PROJECTION

DIMENSIONS ARE IN MILLIMETERS

TOLERANCE UNLESS OTHERWISE SPECIFIED

1 PL +/- 0

2 PL +/- 0

ANGLE +/- 0

JKL

COMPONENTS CORPORATION

TITLE

MINIATURE COLD CATHODE
FLUORESCENT LAMP

DRAWN BY
L. WENGSTROM

APPV'D BY DATE
F.D. 8/1/03

SIZE
A

FSCM NO.
55335

DRAWING NO.

BF3220-29B

RELEASE & CANCEL P-0306-26

8/1/03

REV. NO.

DESCRIPTION/ECO NUMBER

APPV'D DATE

- CAD DRAWING -

MANUAL REVISIONS NOT PERMITTED

SCALE

NONE

RELEASED DATE

8/1/03

REVISION DATE

REV. NO.

SHEET 1 of 1