


| JKL LAMP PART NO. | COLOR LCD HIGH OUTPUT WHITE 8800°k RGB | STARTING CIRCUIT VOLTAGE VS (Vrms) @ 0°C | OPERATING LAMP VOLTAGE VL (Vrms) | OPERATING LAMP CURRENT IL (mAmps) | BRIGHTNESS (CANDELA/m2) | *RATED LIFE (HRS) AVERAGE |
|-------------------|----------------------------------------|------------------------------------------|----------------------------------|-----------------------------------|-------------------------|---------------------------|
| BF3294-24B | x = .285 y = .278 | 1550 | 620 | 5 ± 1 | 28,000 ± 10% | 40,000 |

* RATED LIFE IS DEFINED AS THE POINT AT WHICH THE INTENSITY BECOMES 50% OF THE INITIAL RATING.

| | | | | | | | | | | | |
|----------------------------------------------------------------|--|--|--------------------------------------------------------------------------------------------------------------------------------|--|------------------------------------------------------------------------------------------------------------------|---------------------------------|-----------------------------------|--------------------------|----------------------------------|--|--|
| | | | METRIC  THIRD ANGLE PROJECTION | | DIMENSIONS ARE IN MILLIMETERS TOLERANCE UNLESS OTHERWISE SPECIFIED 1 PL +/- 0 2 PL +/- 0 ANGLE +/- 0 | | JKL COMPONENTS CORPORATION | | | | |
| | | | | | TITLE MINIATURE COLD CATHODE FLUORESCENT LAMP | | | | | | |
| A ELECTRICAL SPEC CHANGES RELEASE & CANCEL P-0308-05 | | | DRAWN BY L. WENGSTROM | | APPV'D BY DATE J.K. 8/5/04 | | SIZE A | FSCM NO. 55335 | DRAWING NO. BF3294-24B | | |
| REV. NO. DESCRIPTION/ECO NUMBER APPV'D DATE | | | - CAD DRAWING - MANUAL REVISIONS NOT PERMITTED | | SCALE NONE | RELEASED DATE 5/17/04 | REVISION DATE 8/5/04 | REV. NO. A | SHEET 1 OF 1 | | |