



JKL PART NUMBER	LENGTH A +/- 2mm	COLOR	STARTING CIRCUIT VOLTAGE VS (Vrms)	OPERATING LAMP VOLTAGE VL (Vrms)	OPERATING LAMP CURRENT IL (mAmps)	BRIGHTNESS (CANDELA/m2)	*RATED LIFE (HRS)
BF659-01A/G	59mm	WARM WHITE	450	190	5 ± 1	5,500 TYP.	20,000
BF6100-01A/G	100mm		550	230	5 ± 1	5,500 TYP.	20,000
BF6120-01A/G	120mm		550	235	5 ± 1	5,500 TYP.	20,000
BF6165-01A/G	165mm		600	255	5 ± 1	5,500 TYP.	20,000

*NOTE: RATED LIFE IS DEFINED AS THE POINT AT WHICH THE INTENSITY BECOMES 50% OF THE INITIAL RATING.

 THIRD ANGLE PROJECTION		DIMENSIONS ARE IN MILLIMETERS TOLERANCE UNLESS OTHERWISE SPECIFIED 1 PL +/- 0.2 2 PL +/- 0 ANGLE +/- 0	<h1>JKL COMPONENTS CORPORATION</h1>	
		TITLE DUAL LEAD TIP TYPE WARM WHITE MINIATURE FLUORESCENT LAMP WITH GROUND STRIP		
DRAWN BY L. WENGSTROM	APPVD BY J.K.	DATE 3/28/05	SIZE A	FSCM NO. 55335
- CAD DRAWING - MANUAL REVISIONS NOT PERMITTED		SCALE NONE	DRAWING NO. BF 6-01A/G	RELEASED DATE 11/27/00
REV. NO.	DESCRIPTION/ECO NUMBER	APPVD DATE	RELEASED DATE 11/27/00	REVISION DATE 3/28/05
			REV. NO. A	SHEET 1 OF 1