



JKL PART NUMBER	COLOR RGB HIGH OUTPUT WHITE 5400°k	STARTING CIRCUIT VOLTAGE VS (Vrms)	OPERATING LAMP VOLTAGE VL (Vrms)	OPERATING LAMP CURRENT IL (mA rms)	BRIGHTNESS (CANDELA/m ²)	*RATED LIFE (HRS)
BF22160-20B	x = .340 y = .360	1065 @ 0°C	355	5 ± 1	38,000 ±10%	20,000

* RATED LIFE IS DEFINED AS THE POINT AT WHICH THE INTENSITY BECOMES 50% OF THE INITIAL RATING.

<p>THIRD ANGLE PROJECTION</p>			<p>METRIC</p> <p>DIMENSIONS ARE IN MILLIMETERS</p> <p>TOLERANCE UNLESS OTHERWISE SPECIFIED</p> <p>1 PL +/- 0.2</p> <p>2 PL +/- 0</p> <p>ANGLE +/- 0</p>		<p>JKL COMPONENTS CORPORATION</p>									
<p>DRAWN BY L. WENGSTROM</p>			<p>APP'VD BY J.K.</p>		<p>DATE 2/18/05</p>		<p>SIZE A</p>		<p>FSCM NO. 55335</p>		<p>DRAWING NO. BF22160-20B</p>			
<p>RELEASED</p>			<p>2/18/05</p>		<p>- CAD DRAWING -</p>			<p>SCALE NONE</p>		<p>RELEASED DATE 2/18/05</p>		<p>REVISION DATE</p>	<p>REV. NO.</p>	<p>SHEET 1 OF 1</p>
<p>REV. NO.</p>	<p>DESCRIPTION/ECO NUMBER</p>				<p>APP'VD DATE</p>	<p>MANUAL REVISIONS NOT PERMITTED</p>			<p>DATE</p>	<p>DATE</p>	<p>NO.</p>	<p>NO.</p>		