


JKL PART NUMBER	COLOR RGB WHITE	STARTING CIRCUIT VOLTAGE VS (Vrms)	OPERATING LAMP VOLTAGE VL (Vrms)	OPERATING LAMP CURRENT IL (mA rms)	BRIGHTNESS (CANDELA/m <sup>2</sup> )	*RATED LIFE (HRS)
BF22316-29B	x = .312 y = .307	1160 @ 0°C	725	5 ± 1	34,000 ±20%	20,000

\* RATED LIFE IS DEFINED AS THE POINT AT WHICH THE INTENSITY BECOMES 50% OF THE INITIAL RATING.

			<b>METRIC</b>  THIRD ANGLE PROJECTION		DIMENSIONS ARE IN MILLIMETERS TOLERANCE UNLESS OTHERWISE SPECIFIED 1 PL +/- REF. 2 PL +/- REF. ANGLE +/- 0		<b>JKL COMPONENTS CORPORATION</b>				
					TITLE <b>MINIATURE COLD CATHODE          FLUORESCENT LAMP</b>						
<b>B</b>	BRIGHTNESS ±20%	6/13/08	DRAWN BY	APPV'D BY	DATE	SIZE	FSCM NO.	DRAWING NO.	<b>BF22316-29B</b>		
<b>A</b>	ADD/CHNG. DIMENSIONS & ELECT. RATINGS	3/21/08	L. WENGSTROM	L.R.	6/13/08	<b>A</b>	<b>55335</b>				
	RELEASE & CANCEL P-0709-05	1/23/08				SCALE	RELEASED DATE	REVISION DATE	REV. NO.	SHEET	
REV. NO.	DESCRIPTION/ECO NUMBER	APPV'D DATE	- CAD DRAWING - MANUAL REVISIONS NOT PERMITTED			NONE	1/23/08	6/13/08	<b>B</b>	1 OF 1	