


JKL PART NUMBER	COLOR GREEN	LAMP WATTS	STARTING CIRCUIT VOLTAGE VS (Vrms)	OPERATING LAMP VOLTAGE VL (Vrms)	OPERATING LAMP CURRENT IL (mAmps)	BRIGHTNESS (CANDELA/m2)	*RATED LIFE (HRS)
BF3165-11B	x = 0.318 ± 0.03 x = 0.556 ± 0.03	1.8	925 @ 0°C	365	5 ± 1	38,000 TYP. 26,600 MIN.	20,000 AVG.

*NOTE: RATED LIFE IS DEFINED AS THE POINT AT WHICH THE OUTPUT BECOMES 50% OF THE INITIAL RATING.

NOTE: ALL SPECIFICATIONS ARE TYPICAL WITH THE LAMP OPERATING, AFTER STABILIZATION, AT AN AMBIENT TEMPERATURE OF 25°C.

METRIC  THIRD ANGLE PROJECTION	DIMENSIONS ARE IN MILLIMETERS TOLERANCE UNLESS OTHERWISE SPECIFIED 1 PL +/- REF. 2 PL +/- REF. ANGLE +/- 0	JKL COMPONENTS CORPORATION					
	TITLE MINIATURE 3.0 GREEN CCFL						
DRAWN BY L. WENGSTROM	APPVD BY DATE J.K. 3/23/05	SIZE A	FSCM NO. 55335	DRAWING NO. BF3165-11B			
- CAD DRAWING - MANUAL REVISIONS NOT PERMITTED		SCALE NONE	RELEASED DATE 10/31/02	REVISION DATE 3/23/05	REV. NO. A	SHEET 1 OF 1	

REV. NO.	DESCRIPTION/ECO NUMBER	APPVD DATE
A	CORRECT ELECTRICAL SPECIFICATIONS PROTOTYPE RELEASE	3/23/05 10/31/02