

JKL LAMP PART NUMBER	COLOR	STARTING CIRCUIT VOLTAGE VS (Vrms)	OPERATING LAMP VOLTAGE VL (Vrms)	OPERATING LAMP CURRENT IL (mArms)	BRIGHTNESS (CANDELA/m2)	*RATED LIFE (HRS)
BF3240-24B	LCD HIGH OUTPUT WHITE 7400°k RGB	1150 @ 0°C	480	5 ± 1	28,000 ± 10%	20,000

^{*} RATED LIFE IS DEFINED AS THE POINT AT WHICH THE INTENSITY BECOMES 50% OF THE INITIAL RATING.

		METRIC	DIMENSIONS ARE IN MILLIMETERS	_1	IKI	[corner	VENTE COR	POP 4	ELON	
	1		\oplus	TOLERANCE UNLESS OTHERWISE SPECIFIED 1 PL +/- 0	COMPONENTS CORPORATION MINIATURE COLD CATHODE					HON
			THIRD ANGLE PROJECTION	2 PL +/- 0 ANGLE +/- 0	FLUORESCENT LAMP					
	RELEASE AND CANCEL P-0105-05	8/1/01	L. WENGSTROM	APPV'D BY DATE FD 8/2/01	SIZE A	55335		3240-24B		
REV NO.		APPV'D DATE	- CAD DRAWING - MANUAL REVISIONS NOT PERMITTED		SCALE	NONE	RELEASED 8/1/01	REVISION DATE	REV. NO.	1 OF 1