

JKL LAMP PART NUMBER	COLOR RGB WHITE	STARTING CIRCUIT VOLTAGE VS (Vrms)	OPERATING LAMP VOLTAGE VL (Vrms)	OPERATING LAMP CURRENT IL (mArms)	BRIGHTNESS Cd/m2 @ 25°C	*RATED LIFE (HRS)	
BF48340-39B 6,200 KELVIN x = .323 / y = .309		1,365 @ 25°C	545	5 ± 1	10,000 TYP. 7,000 MIN.	20,000 (AVG.) 10,000 (MIN.)	

^{*} RATED LIFE IS DEFINED AS THE POINT AT WHICH THE INTENSITY BECOMES 50% OF THE INITIAL RATING.

NOTE: ALL SPECIFICATIONS ARE TYPICAL WITH THE LAMP OPERATING, AFTER STABILIZATION, AT AN AMBIENT TEMPERATURE OF $25^{\circ}\mathrm{C}.$

			METRIC	IN MILLIME	DIMENSIONS ARE IN MILLIMETERS		COMPONENTS COPPORATION					
			THIRD ANGLE PROJECTION	TOLERANCE UNLESS OTHERWISE SPECIFIED 1 PL +/- 0 2 PL +/- 0 ANGLE +/- 0								1011
	DELEACE & CANCEL DOMAS OF	2/45/05	DRAWN BY L. WENGSTROM	APPV'D BY J.K. 3/	DATE /15/05	SIZE A	55335		BF	48340-39B		
REV. NO.	RELEASE & CANCEL P-0412-06 DESCRIPTION/ECO NUMBER	3/15/05 APPV'D DATE	- CAD DRAWING - MANUAL REVISIONS NOT PERMITTED			SCALE		RELEASED DATE 3	/15/05	REVISION DATE	REV. NO.	SHEET 1 OF 1