



JKL PART NUMBER	LENGTH A +/- 2mm	COLOR 5200° KELVIN	STARTING CIRCUIT VOLTAGE VS (Vrms)	OPERATING LAMP VOLTAGE VL (Vrms)	OPERATING LAMP CURRENT IL (mA rms)	BRIGHTNESS (CANDELA/m2)	*RATED LIFE (HRS)
BF8300-20A	300mm	LCD HIGH OUTPUT WHITE	1200	390	5 ± 1	4,000	20,000

* NOTE: RATED LIFE IS DEFINED AS THE POINT AT WHICH THE INTENSITY BECOMES 50% OF THE INITIAL RATING.

METRIC

THIRD ANGLE
PROJECTION

DIMENSIONS ARE
IN MILLIMETERS

TOLERANCE UNLESS
OTHERWISE SPECIFIED

1 PL +/- 0.2
2 PL +/- 0
ANGLE +/- 0

DRAWN BY
L. WENGSTROM

APP'VD BY DATE
J.K. 8/12/03

- CAD DRAWING -
MANUAL REVISIONS NOT PERMITTED

JKL COMPONENTS CORPORATION

TITLE
DUAL LEAD LOW PROFILE TIP TYPE HIGH
OUTPUT WHITE MINIATURE FLUORESCENT

REV. NO.	DESCRIPTION/ECO NUMBER	APP'VD DATE	SCALE	SIZE	FSCM NO.	DRAWING NO.	RELEASED DATE	REVISION DATE	REV. NO.	SHEET
		8/12/03	NONE	A	55335	BF8300-20A	8/12/03			1 of 1