


JKL LAMP PART NUMBER	COLOR	STARTING CIRCUIT VOLTAGE VS (Vrms)	OPERATING LAMP VOLTAGE VL (Vrms)	OPERATING LAMP CURRENT IL (mArms)	BRIGHTNESS (CANDELA/m ²)	*RATED LIFE (HRS)
CF24236-24B	WHITE 7,570°k x = .300 y = .308	1260 TYP. @ 0°C	516	5.0	32,000±10%	50,000
			501	6.5	38,000±10%	30,000

* RATED LIFE IS DEFINED AS THE POINT AT WHICH THE INTENSITY BECOMES 50% OF THE INITIAL RATING.

			METRIC  THIRD ANGLE PROJECTION		DIMENSIONS ARE IN MILLIMETERS TOLERANCE UNLESS OTHERWISE SPECIFIED 1 PL +/- 0.3 2 PL +/- 0.2 ANGLE +/- 0		JKL COMPONENTS CORPORATION				
					TITLE MINIATURE COLD CATHODE FLUORESCENT LAMP						
			DRAWN BY L. WENGSTROM		APPVD BY DATE J.K. 1/20/04		SIZE A	FSCM NO. 55335	DRAWING NO. CF24236-24B		
RELEASED			1/20/04		- CAD DRAWING - MANUAL REVISIONS NOT PERMITTED		SCALE NONE	RELEASED DATE 1/20/04	REVISION DATE	REV. NO.	SHEET 1 OF 1
REV. NO.	DESCRIPTION/ECO NUMBER		APPVD DATE								