

NOTES:


1. LED includes integrated diode for reverse voltage protection.
2. LED includes integrated resistor for current limiting.

Operating Temperature Range	-30°C to +85°C
Storage Temperature Range	-40° to +100°C

TYPICAL ELECTRICAL & OPTICAL OPERATING CHARACTERISTICS

(Ta = 25 degree C)

PART NUMBER	EMITTING COLOR	AMPERAGE mA	VOLTAGE Vdc	LUMENS	DOMINANT WAVELENGTH	VIEWING ANGLE DEGREES
LE-0504-06W	9000°K WHITE	20mA	6.0	2.00	x = 0.28 y = 0.28	95

			<div>METRIC</div> <div></div> <div>THIRD ANGLE PROJECTION</div>	<div>DIMENSIONS ARE IN MILLIMETERS</div> <div>TOLERANCE UNLESS OTHERWISE SPECIFIED</div> <div>1 PL +/- 0.2</div> <div>2 PL +/- 0.20</div> <div>ANGLE +/- 0</div>	<div>JKL COMPONENTS CORPORATION</div> <div>TITLE</div> <div>T-1 3/4 WEDGE BASE 6 VOLT LED</div>										
					SIZE	FSCM NO.	DRAWING NO.								
B	ADD 9000°K WHITE TO EMITTING COLOR		6/22/10	DRAWN BY	APPV'D BY	DATE	A	55335	LE-0504-06						
A	CHANGE CHART		8/25/08	L. WENGSTROM	L.R.	6/22/10									
	ENGR RELEASED		7/16/07				SCALE	RELEASED DATE		7/16/07	REVISION DATE	6/22/10	REV. NO.	B	SHEET 1 OF 1
REV. NO.	DESCRIPTION/ECO NUMBER		APPV'D DATE	- CAD DRAWING - MANUAL REVISIONS NOT PERMITTED			NONE								