



JKL LAMP NUMBER	VOLTS RATED	AMPS ±10%	MSCP ±25%	LUMENS ±25%	AVERAGE LIFE HRS.	FILAMENT TYPE
8732	2.5	.100	.100	1.25	10,000	C-2R
7207	3.0	.060	.030	0.38	60,000	C-2R
CW43	5.0	.030	.016	0.20	25,000	C-2V
7210	5.0	.030	.030	0.38	16,000	C-2R
683	5.0	.060	.050	0.63	25,000	C-2R
713	5.0	.075	.090	1.13	25,000	C-2R
715	5.0	.115	.150	1.89	40,000	C-2R
7213	5.0	.115	.200	2.51	5,000	C-2R
7216	5.0	.125	.220	2.77	5,000	C-2R
CW79	6.0	.065	.110	1.40	10,000	C-2R
CW85	8.0	.050	.095	1.19	10,000	C-2V
7218	10.0	.027	.100	1.26	10,000	C-2F
CW04	12.0	.055	.180	2.26	5,000	C-2V
7219	12.0	.060	.150	1.89	10,000	C-2F
CW1345	13.0	.045	.150	1.89	10,000	C-2F
23	14.0	.040	.150	1.89	16,000	C-2F
8111	14.0	.065	.150	1.89	10,000	C-2F
CW11	14.0	.065	.199	2.50	5,000	C-2F
7220	18.0	.026	.150	1.89	10,000	C-2F
6838	28.0	.024	.150	1.89	4,000	CC-2F

P	Ch MOL to 7.0mm	11/3/20
O	DELETE CW81, 7208, CW23, 6022, 680, 6150, CW44, CW145 CHNG LIFE HRS. LAMPS 7207, 683, 7219, 8111, 7220,	11/6/19
N	CHANGE DIM. 6.35 MAX. TO 6.75 MAX.	1/3/17
M	CHANGE LEADS TO 25.4 MIN	10/4/11
L	ADD LAMP CW11	8/15/01
K	ADD LAMPS CW81, CW79 & CW1345	02/14/00
J	LEAD LENGTH 38.1 MIN. TO 38.1±6.35, Ø0.25 ADD REF.	02/03/00
I	DRAW CONVERTED TO CAD-LEAD LENGTH TO 38.1 MIN.- DELETED 7203, 7205, CW27, 8729, CW55, CW45, CW16	01/01/00
H	LEAD LENGTH 1.50±.250 TO 1.00 MIN.	7/15/99
	RELEASED	1973
REV. NO.	DESCRIPTION/ECO NUMBER	APPV'D DATE

**METRIC**

DIMENSIONS ARE IN MILLIMETERS

TOLERANCE UNLESS OTHERWISE SPECIFIED

1 PL +/- 0.2

2 PL +/- 0.20

ANGLE +/- 0

THIRD ANGLE PROJECTION

DRAWN BY L. WENGSTROM

APPV'D BY S.C.N. DATE 11/6/19

- CAD DRAWING -  
MANUAL REVISIONS NOT PERMITTED

**JKL** COMPONENTS CORPORATION

TITLE: T-1 STANDARD WIRE TERMINAL LAMP MULTI LISTING

**WIRE TERMINAL T-1**

SIZE **A** FSCM NO. **55335** DRAWING NO.

SCALE NONE

RELEASED DATE 1973

REVISION DATE 11/3/20

REV. NO. P

SHEET 1 OF 1