LED 12V 100 WATT POWER SUPPLY

CC.

FEATURES

UL/cUL/CE and RoHS CERTIFICATIONS

OUTDOOR IP67 WATERPROOF

COMPACT DESIGN: 196mm X 68mm X 40mm

SPECIFICATIONS

OUTPUT DC VOLTAGE



8.4A
100 WATTS
<100mVp-p
11.4V-12.6V 0~16.8A
<1%
<5%
-

INPUT

VOLTAGE RANGE	100-264VAC				
FREQUENCY	50-60Hz				
EFFICIENCY (TYP)	0.87				
AC CURRENT	1.4A MAX/100VAC				
INRUSH CURRENT	30A MAX/100-240VAC input at cold start 25°C				
LEAKAGE CURRENT <0.25mA					

PROTECTION

SHORT CIRCUIT	No damage should occur due to any output operating under a short circuit condition. The power						
SHORT CIRCUIT	supply will self-recover once the fault condition is removed.						
OVER VOLTAGE	Protection type: Shut down and latch off o/p voltage, re-power to recover.						

ENVIRONMENT

WORKING TEMPERATURE	0°C ~ 40°C			
WORKING HUMIDITY	10%~90%			
STORAGE TEMP/HUMIDITY	-30°C~+70°C			
VIBRATION 1.0mm, 10-25 Hz, 15 minutes per cycle for each axis (X, Y, Z)				

SAFETY and EMC

SAFETY STANDARD	EN61347-1, /-2-13 UL 8750 + UL 60950						
EMI CONDUCTION and RADIATION	The power supply met the radiated and conducted emission requirements for FCC PART 15B						
EMI CONDUCTION and RADIATION	Class B, EN55015						

OTHERS

MTBF	550,000 Hours
Life Tíme	68,000 Hours
Shell Material	Aluminum

PART NO.: ZCV-12100

			THIRD ANGLE PROJECTION	OTHERWISE 1 PL +/- 2 PL +/- ANGLE +/-	- REF. - REF.	12V 100 WATT LED POWER SUPPLY						
	RELEASED	8/12/15	DRAWN BY L. WENGSTROM	APPV'D BY L.R.	DATE 8/12/15	SIZE A	FSCM NO. 55335	DRAWING NO.	ZC	V-12100		
REV. NO.	DESCRIPTION/ECO	APPV'D DATE	- CAD DI MANUAL REVISION	RAWING - NS NOT PE	-	SCALE		RELEASED DATE 8	/12/15	REVISION DATE	REV. NO.	SHEET 1 _{OF} 1