
## FEATURES 12VDC 170° WIDE BEAM HIGH-OUTPUT LED CHANNEL for SMALL/MEDIUM CHANNEL LETTERS and SIGN BOXES

IP67
50,000 Life Hours/5 Year Warranty
Operating Temperature -20°C to +70°C
170° Wide Beam
50 Modules per Strand


## 12.6mm (.496") edge to edge 10mm (.393") edge to center hole







Note: Height is 8.98 mm (.35") with mounting tape attached



## NOTES:

Mounting can be accomplished with double sided tape that is on the backside of modules. Screw holes are also present. Wire with Red Stripe is Positive Input. Use no more than 50 modules in series.

Take care to prevent exposed wire on the ends.



JKL	Input	Power per	Color	Beam	Lumen Flux	No. Modules Per
Part Number	Voltage	Module		Angle	per Module	Pack
ZM-333-B	12V DC	0.66W	BLUE - 465nm	170°	12 lm	50 pc/24.6' (7.5 Meters)

			METRIC	ı		NS ARE ICHES)	`		COM	DO.	IENITO CO		TION
			<del>  (1)                                   </del>	TOLERANCE UNLESS OTHERWISE SPECIFIED 1 PL +/- REF. 2 PL +/- REF. ANGLE +/-		COMPONENTS CORPORATION							
			THIRD ANGLE PROJECTION				W	WIDE BEAM BLUE LED CHANNEL MODULE					JLE
$\vdash$			DRAWN BY	APPV'D	BY	DATE	SIZE	FSCM NO.	DRAWING				
		5/10/23	S Newton	١٧٧	5/1	0/23	lΑ	55335	NO.	ZM	-333-B		
	Released						SCALE		RELEASED		REVISION	REV.	SHEET
REV. NO.	DESCRIPTION/ECO NUMBER	APPV'D DATE					OOALL	NONE	DATE 5/10/		REVIOION	NO.	1 of 1