SPECIFICATIONS

1.	WIRE SIZE:	24 AWG
2.	NO. OF CONDUCTORS:	1
3.	NO. OF STRANDS:	19
4.	NOM. SIZE OF STRAND:	36 AWG
5.	FINISH OF STRAND:	SILVER
6.	INSULATION MATERIAL:	SILICONE
7.	INSULATION COLOR:	PINK/RED
8.	NOM. THK. INSULATION:	0.68 mm (0.027 IN)
9.	NOM. FINISHED CABLE O.D.:	2.00 mm (0.078 IN)
10.	TEMPERATURE RANGE:	-65°C TO 200°C
11.	VOLTAGE RATING:	5,000 VOLTS DC
12.	UL TYPE:	UL3239
13.	PACKAGING:	1000 FOOT REEL

JKL PART NO.: RM-UL3239-24-PNK-5KV

REV. NO.	DESCRIPTION/ECO NUMBER	APPV'D DATE
B	CHANGE NOM THK INSULATION	4/17/14
A	NEW CAD DRAWING	3/13/12
	RELEASED	6/16/03

METRIC
THIRD ANGLE PROJECTION

DIMENSIONS ARE IN MILLIMETERS
TOLERANCE UNLESS OTHERWISE SPECIFIED
1 PL +/- 0.2
2 PL +/- 0.20
ANGLE +/-

JKL COMPONENTS CORPORATION

TITLE: UL3239-24 PINK WIRE

DRAWN BY	APPV'D BY	DATE	SIZE	FSCM NO.	DRAWING NO.
L. WENGSTROM	L.R.	4/17/14	A	55335	RM-UL3239-24-PNK-5KV

- CAD DRAWING -
MANUAL REVISIONS NOT PERMITTED

SCALE	RELEASED DATE	REVISION DATE	REV. NO.	SHEET
NONE	3/9/11	4/17/14	B	1 OF 1